

Openview SDK 1.0 Release

Notes

- **Important note:** InstallOpenViewSDK64.exe will include documentation and sample application. This executable should be used for development of your application. The InstallOpenView64.exe does not include the documentation and sample.
- **Important Installation note:** To update OpenView SDK from version 1.0R8 or earlier, Uninstall the older version then install the new version.

OpenView SDK 1.0R20

2019-01-22

New Features

- 36085 - Silent installer does not upgrade from a previous version.
- 35927 - Negative start time crash.

Bug Fixes

- Add the possibility to separate the A-Scan start and TCG start, allowing to have an A-Scan starting at the main bang while the TCG starts at the front wall.

OpenView SDK 1.0R19

2018-12-11

New Features

- 35949 - Add 25 ns pulse width option and extended BW option;
- 35949 - Add band pass Filter 11 MHz (1.1-20.5MHz) option

Note: These options need to be unlocked by Olympus factory.

OpenView SDK 1.0R18

2018-11-29

-
- Demo version

OpenView SDK 1.0R17

2018-11-19

Bug Fixes

- 35748 - When Focus PX hard drive D is full the Software cannot be Deploy.
- 36078 - Encoder does not reset.

OpenView SDK 1.0R16

2018-10-31

- Pre-release version for storage demo,

OpenView SDK 1.0R15

2018-10-10

Bug Fixes

- 36006: Exception on acquisition start while switching contexts.

OpenView SDK 1.0R14

2018-09-24

Bug Fixes

- 36001: Switching from UT to PA back to UT may restrict Pitch-Catch selection

OpenView SDK 1.0R13

2018-09-19

- Removed 32 bits support

Bug Fixes

- 35984: Beam with amplitude near to 0 give a gain problem.
- 35930: Installing the 1.0R13 will now correctly uninstall previous versions of OpenView
- Enforce a device to be reprogrammed when switching acquisitions to prevent undefined behavior
- Fix crash that happened while changing layouts too quickly.

OpenView SDK 1.0R11

2018-08-21

Bug Fixes

- 35838: DigitalOutput: SetState; Getting the state of digital output pin did not have always the good value.
- 35880: Change from Log to Lin Fix.

Bug Fixes

- 35854: Law file element offset is not taken into account.

OpenView SDK 1.0R9

2018-07-19

New Features

- Sample application
- support private IP addresses other than 192.168.0.1
- Noticed we were not using the extra feature set from the .Net 4.5 framework so we lowered our references from 4.5 to 4.0 which means that if you wish to use the SDK in .Net it would work in Visual Studio 2010.

Bug Fixes

- 35786 - Echo synchronisation mode with TCG

OpenView SDK 1.0R8

2018-07-12

New Features

- Configuration Tool (FocusPC version)
- Diagnostic tools
- Support 65535 flag in law file import (TTU)
- Need an installer containing only runtime libraries
- New installer has slightly changed as it comes in 4 versions
 - 32 and 64 bits
 - Programmer and End-User

*To integrate them correctly refer to technical note in the

[Appendix for OpenView SDK 1.0R8 and newest version: of this document.](#)

We deprecated some functions from the previous version. The functions can still be used but will generate a “warning: deprecated” indication. If this creates compiler errors, please verify the following in the project’s properties:

- *Treat Warnings As Errors* should be set to *No*
- *SDL Checks* should be set to *No*

Bug Fixes

- None

OpenView SDK 1.0R7

2018-06-21

New Features

- High Dynamic range
- Multi-device support

Bug Fixes

- 35617 - No beams have been applied error (manual recurrence)
- 35406 - Code snippets fix
- 35682 - [UT Settings] Pulse Width value causes ApplyConfig error

OpenView SDK 1.0R6

2018-05-22

New Features

- Library integration compilation specificity
- Multi-user accounts environment

Bug Fixes

- 35413 Recurrence in Manual Mode
- 35538 Installation shows error 1152
- 35539 Encoders going backward issue
- 35615 Improvement of the deployment process stability

General information:

The OpenView SDK (SDK: Software Development Kit) is designed for the integration of FocusPX in custom software environments. OpenView SDK is mainly used for the development of application-dedicated software interface and system automation.

Compatible Programming Languages (64-bit)

- C++
- C#
- LabVIEW

Supported Acquisition Units

- UT4
- FOCUS PX 16:64PR
- FOCUS PX 16:128PR
- FOCUS PX 32:128PR

Supported Operating Systems

- Microsoft Windows 10 (64-bit)
- Microsoft Windows 7 (32-bit and 64-bit)

Note: You must have administrator privileges to install Openview SDK and configure the computer for data acquisition.

Computer Requirements

- **CPU:** Intel Core i7 or Xeon E3
- **RAM:** 16 GB (DDR3 or better)
- **Data storage drive:** SSD
- **Network adaptor:** Gigabit Ethernet card (dedicated for FOCUS PX)
- **Display:** 1280 × 1024 or higher
- One USB port for the HASP security hardware key
- A keyboard and a pointing device

Available in standard Languages

End-user requirements for software using OpenView SDK

This section promotes the best practices recommended while integrating OpenView SDK to your software.

Required Firewall Rules

The following table lists all ports to enable during the installation of your software. The second column shows the command to execute when adding a firewall rule for the corresponding port.

Port	Command
21	netsh advfirewall firewall add rule name="Olympus OpenView SDK" dir=in action=allow protocol=TCP localport=21
67	netsh advfirewall firewall add rule name="Olympus OpenView SDK" dir=in action=allow protocol=UDP localport=67
68	netsh advfirewall firewall add rule name="Olympus OpenView SDK" dir=out action=allow protocol=UDP remoteport=68
9994	netsh advfirewall firewall add rule name="Olympus OpenView SDK" dir=out action=allow protocol=TCP remoteport=9994,10994,12000,27015
10994	
12000	
27015	

End-user Installer

There are 2 installers available for OpenView.

Installer	Description
InstallOpenViewSDK-1.0RXXX.exe	To be installed on the programmer's computer. Includes libraries, documentation and code snippets. This installs on C:\OlympusNDT.
InstallOpenView-1.0RXXX.exe	To be installed on the end-user's computer. Includes libraries only. This installs on C:\Program Files.

Integrators must integrate the end-user's installer into their own installer. Locating and accessing the libraries at runtime requires the use of one of those keys:

Installer	Key
InstallOpenViewSDK-1.0RXXX.exe	HKEY_LOCAL_MACHINE\SOFTWARE\OlympusNDT\OpenView SDK\1.0\VersionPath
InstallOpenView-1.0RXXX.exe	HKEY_LOCAL_MACHINE\SOFTWARE\OlympusNDT\OpenView\1.0\VersionPath

Each installer automatically configures the value of those keys.

To make an installer silent you need to add the command line arguments: /s /v/qn

Firmware Package

SDK versions and software packages used by the FocusPX are bundled together. Since the SDK always uses the package used on the computer, the application code should search for the latest version installed. Here is a sample code showing good practice.

```
// Select the latest version of firmware packages.
shared_ptr<IFirmwarePackage> package;
auto packages =
IFirmwarePackageScanner::GetFirmwarePackageCollection();    if
(!packages.empty() )    package = packages->GetFirmwarePackage(0);

if (package == nullptr)
    throw std::exception("Could not find the firmware package.");

// Start the package on the device.
if (!device->HasPackage(package))
device->Download(package);

device->Start(package);
```


Config Tool

The configuration tools is installed by the end-user's installer and the root directory is located at the content of registry key :

Installer	Key
InstallOpenViewSDK-1.0RXXX.exe	HKEY_LOCAL_MACHINE\SOFTWARE\OlympusNDT\OpenView SDK\1.0\VersionPath
InstallOpenView-1.0RXXX.exe	HKEY_LOCAL_MACHINE\SOFTWARE\OlympusNDT\OpenView\1.0\VersionPath

The folders “\Tools\Configuration” must be added to this root directory. The program name is ConfigurationTool.exe.

We recommend adding a link in your software to call this configuration tool. The link should show Microsoft shield icon indicating the administrative rights may be required.



IMPORTANT: The tool should be called prior to any other SDK calls since it may change some network settings and test connection with devices.